

Standards Comco-PA6G Dimensions



Sheets

Thickness (mm)	weight (kg / piece)	
	2000 x 1000 mm	3050 x 1220 mm
20	54,0	96,3
25	68,0	116,4
30	80,0	142,2
35	92,0	163,8
40	106,0	187,2
45	117,0	210,0
50	130,0	231,6
55	144,0	254,9
60	156,0	276,0
65	167,6	-
70	180,0	345,0
75	195,0	-
80	208,0	399,0
85	221,0	-
90	234,0	-
95	247,0	-
100	260,0	-

Sheets

Thickness (mm)	weight (kg / piece) 1000 x 1000 mm
110	138,8
115	145,1
120	151,4
125	157,7
130	164,1
140	176,7
150	189,9
160	201,9

tolerances in thickness according DIN 16986, tolerances in length - 0 / + 3 %, tolerances in width + 5 / + 25 mm. Appr. Production weights.

Blocs and special dimensions on request. Send us your inquiry.

Rods

Diameter (mm)	weight (kg / piece) L = 1000 mm	Diameter (mm)	weight (kg / piece) L = 1000 mm
50	2,5	230	51,0
55	2,9	240	56,0
60	3,5	250	63,0
65	4,2	260	67,0
70	4,8	270	72,0
75	5,6	280	78,0
80	6,2	290	82,0
85	7,0	300	88,5
90	7,8	310	93,0
95	9,0	320	99,0
100	9,9	325	104,0
105	11,0	330	105,0
110	11,8	340	113,0
115	13,0	350	120,0
120	14,2	360	126,0
125	15,5	370	132,0
130	16,8	375	136,0
135	18,0	380	140,0
140	19,0	390	152,0
145	20,8	400	155,0
150	21,6	410	166,0
155	24,0	420	174,5
160	24,8	425	176,5
165	26,5	430	185,0
170	27,8	440	188,0
175	30,0	450	197,0
180	31,8	460	206,0
190	35,0	470	217,5
200	38,5	475	218,0
210	42,8	480	228,0
220	47,0	490	235,0
225	49,0	500	242,0

tolerances in Diameter according DIN 16980, tolerances in length - 0 / + 3 %. Appr. Propduction weights.

Rods and Discs are available up to diameter Ø 2100 mm. Send us your inquiry.